



# ATV Xtreme®

## Synthetic Blend Four-Stroke ATV Gasoline Engine Oil

### General Description

Formulated with the very latest in lubricant technology for ATV four-stroke gasoline engines, Cenex® ATV Xtreme® is a synthetic blend that provides superior performance in all ATV gasoline engines. Based on an optimized blend of synthetic and low volatility mineral base oils, ATV Xtreme delivers exceptional low temperature pumpability, as well as superior resistance to high temperature oxidation and volatility in high-performance ATV engines.

ATV Xtreme is designed for long engine life under heavy duty ATV gasoline engine service. Additionally, it's unique formulation provides excellent transmission wet clutch performance as well for those ATV's using one oil for both crankcase and transmission service.

The wide temperature operational range of Cenex ATV Xtreme SAE 5W-40 allows you to use one oil year-round in all types of weather extremes and is recommended in all four-stroke ATV gasoline engines.

### Features and Benefits

- **Application:** Recommended for all makes of four-stroke ATVs including Polaris, Yamaha, Arctic Cat, Kawasaki, Honda, Can-AM, Bombardier and Suzuki.
- **Performance:** Proven formula provides API SN and JASO MA performance ensuring superior engine protection and longer transmission and wet clutch life in ATV's using one all season oil for both engine and transmission service.
- **Oil Pumpability:** Oil that pumps better than required will be circulated from the crankcase to various engine areas faster during cold startups, therefore, preventing wear. Provides cold start to -35° F.
- **Lower Volatility:** The use of selected synthetic and low volatility base oils reduces the amount of high temperature "burn-off", limits oil consumption and reduces high temperature deposits.
- **Shear Stability:** High shear stability limits viscosity loss from shear stress in the engine.
- **Oxidation Control:** Excellent oxidation protection for high operating temperatures experienced by modern ATVs.
- **Rust Control:** Provides extra rust protection for extreme environments and extended periods of storage.
- **Balanced Formula:** Special friction characteristics for excellent transmission and wet clutch performance for ATVs using one oil for both crankcase and transmission.
- **Anti-wear Protection:** Reduces wear, protecting high load engine parts at both high and low speeds.

# ATV Xtreme®

---

## Synthetic Blend Four-Stroke ATV Gasoline Engine Oil

### Typical Applications

Cenex ATV Xtreme® provides superior performance in all makes of ATVs.

### Typical Customers

Owners/operators of all gasoline engine ATVs.

### Typical Properties

SAE Grade	5W-40
API Gravity / lbs./gal.	32.5 / 7.18
Flash Point, °C (°F)	210 (410)
Viscosity @40°C, cSt (SUS)	84.7 (403)
Viscosity @100°C, cSt (SUS)	14.5 (77)
Viscosity Index	179
CCS Viscosity, cP @ -30° C (SAE5W)	5,600
Viscosity @-35°C, cP (MRV-TP1)(SAE 5W)	36,000
Pour Point, °C (°F)	-39 (-38)

The typical properties listed reflect the general characteristics of the product, and are not manufacturing specifications. Normal batch-to-batch variations should be expected.

### Health & Safety

A complete safety data sheet is available by calling 1-651-355-8438 or visit [cenex.com/sds-library](http://cenex.com/sds-library).